



Grade 5 Chromium Steel Balls:
High precision balls are within 5/1,000,000" round. These are military level specification, used for precision equipment. R-64 hardness, of the highest grade.

52100 High Carbon Chromium Alloy Races:
Vacuum de-gassing process for the purest chromium alloy steel, hardened to R-62, extremely tough and very durable. Polished to a mirror finish for ABEC-5 precision and noiseless movement.

To meet the ABEC-5 standard, bearing design must pass all tests, which include noise testing at high RPM, extremely close tolerances for I.D. and O.D., roundness of ball, trueness of the races and micro surface finishes of balls and races. All ABEC 5 bearings are filled both sides with Kluber Isoflex grease.

ABEC 5 Bearings	Static Capacity (lbs)	Weight (grams)	Dimensions IDxODxWidth	Application
-----------------	-----------------------	----------------	------------------------	-------------

New Item

608 SRS	315	11.2	8 x 22 x 7	
688 LLB A5	135	3.7	8 x 16 x 5	
699 LLB A5	225	7.1	9 x 20 x 6	
61801 SRS	233	5.9	10 x 19 x 7	
61802 SRS	281	6.6	15 x 24 x 5	
61803 SRS	421	7.2	17 x 26 x 5	
61804 SRS	438	17.9	20 x 32 x 7	
61805 SRS	563	20.4	25 x 37 x 7	
61806 SRS	685	24.6	30 x 42 x 7	
61808 VV	823	30.9	40 x 52 x 7	

61900 SRS	303	8.8	10 x 22 x 6	
61901 SRS	318	10.7	12 x 24 x 6	
61902 SRS	434	15.1	15 x 28 x 7	
61903 SRS	477	15.9	17 x 30 x 7	
61903/29.5 LLB	477	15.0	17 x 29.5 x 7	

61000 SRS	438	16.9	10 x 26 x 8	
61001 SRS	500	20.9	12 x 28 x 8	
61002 LLB	563	27.4	15 x 32 x 9	

R 6 SRS	304	11.1	3/8 x 7/8 x 9/32"	
R 8 VV A5	500	21.0	1/2 x 1 1/8 x 5/16"	
B 542 2RS-R	1115	24.8	1-5/16 x 1-3/4 x 9/32"	

ABEC 5 Bearings	Static Capacity (lbs)	Weight (grams)	Dimensions IDxODxWidth	Application
-----------------	-----------------------	----------------	------------------------	-------------

New Item

MR 15267 LLU A5	390	11.2	15 x 26 x 7	
MR 17287 LLB A5	418	13.6	17 x 28 x 7	
MR 18307 LLB A5	438	15.1	18 x 30 x 7	
MR 22378 LLB A5	688	27.2	22 x 37 x 8	
MR 2437 LLB A5	726	31.0	24 x 37 x 7	

Angular Contact Series

This new addition to the Enduro line reflects the need for adjusting the play out of wheels, especially with disc brakes on roadbikes. The hubs require a preload feature in order to utilize these bearings. We now have wave washers in fitments section

- These bearings are made with a 15 degree contact angle
- They are dimensionally the same as the 61xxx series bearings
- They are all ABEC-5 Quality Bearings
- Load side on RED seal side; .5-1 NM preload required

ABEC 5 Bearings	Static Capacity (lbs)	Weight (grams)	Dimensions IDxODxWidth	Application
-----------------	-----------------------	----------------	------------------------	-------------

New Item

Enduro ABEC 5 Angular Contact Series

71900 LLB	348	8.8	10 x 22 x 6	
71801 LLB	216	5.9	12 x 21 x 5	
71901 LLB	365	10.3	12 x 24 x 6	
71001 LLB	620	19.0	12 x 28 x 8	
71802 LLB	252	6.9	15 x 24 x 5	
MRA 1526 LLB	390	11.2	15 x 26 x 7	
71902 LLB-N	499	15.0	15 x 28 x 7	
71803 LLB	317	7.6	17 x 26 x 5	
MRA 1728 LLB	418	13.6	17 x 28 x 7	
71903 LLB	548	15.3	17 x 30 x 7	
71804 LLB	504	16.4	20 x 32 x 7	
MRA 2437 LLB	726	31.0	24 x 37 x 7	
71805 LLB	647	19.2	25 x 37 x 7	
71806 LLB	747	22.4	30 x 42 x 7	